



Qty.	'A'	'B'	'C'	Options / Accessories	Tag

STANDARD CONSTRUCTION

- Fabricated of 18 gauge galvanized steel. All seams are fully welded and sprayed with protective coating.
- Mill finish is standard
- If either dimension exceeds 90", multisection construction may be required.

PROJECT: _____
 LOCATION: _____
 ARCHITECT: _____
 ENGINEER: _____
 CONTRACTOR: _____
 PO NUMBER: _____
 DATE: _____

OPTIONS / ACCESSORIES

MATERIAL

Steel products are available in various gauges of galvanized, galvaneal, or stainless.

LINERS

A liner may be used for retention of insulation or as support to strengthen large units that will support a heavy load. Liners are manufactured as an integral part of the product to add maximum structural support.

CURB CAP

Standard curb cap of 2-3/4" can be replaced by 4-1/2" or other sizes by specifying.

PLATFORM CAP

A 3/4" plywood top with a metal cap fabricated of the same material as the product.

WOOD NAILER

Factory installed wood nailer for equipment mounting is mechanically fastened to top perimeter.

GASKET

1/4" thick polyurethane foam gasket can be installed, lining the entire top perimeter.

INSULATION

Available with 1" or 2" semi-rigid insulation.

ACCESS PANELS

To provide a passageway to internal equipment, an access opening is cut and lined with a protective vinyl edge seal and the cover panel is mechanically fastened over the opening. Minimum height restrictions apply.

LOUVERED VENTS

To provide an airflow through the curb, units are available with 6"W x 7/8" high louvered vents, with 4 per side. Minimum height restrictions apply.

DAMPER RACK

For mounting of dampers in the curb, a damper rack can be installed. The rack is located in the bottom of the curb and a damper is then mounted on top of the rack. Damper and/or rack flange dimensions must be specified.

SECURITY BARS

Selections of bar diameters, frame styles, and spacing are available.

FINISHES

A wide selection of finishes including baked enamel, epoxy, or prime coat.