



Temporary Climate Control Solutions for Commercial & Industrial Applications



A PERMANENT PART OF
YOUR TEMPORARY SOLUTIONS



We're More than a Portable Spot-Cooling Solutions Provider, **WE'RE YOUR PARTNER.**

The best business relationships bring more than products to the table. They bring you job-specific solutions and the technical support that gives you the confidence you deserve. With more than 60 years of experience, Koldwave is dedicated to supporting the business goals of our customers with the most durable, dependable temporary spot-cooling solutions available.

A leader in air- and water-cooled portable air conditioning solutions, Koldwave's comprehensive selection of state-of-the-art equipment is ready to go upon delivery and capable of addressing the full spectrum of temporary, spot, and emergency HVAC cooling applications.

Koldwave takes responsibility for the solutions we provide, working with you to determine which units best fit your operational model and meet your customer's needs. All of our solutions are backed by reliable technical service and support. We even leverage our market insights to help you effectively sell our equipment.



Koldwave Portable Spot Cooling Applications

LIKE YOU, KOLDWAVE STAYS COOL UNDER PRESSURE.

Regardless of the situation, your customers are looking for solutions that address a variety of applications. So, it's important to have the right fleet of systems at your disposal to ensure you can address the unique range of portable spot cooling applications your customers will throw at you.

As a leading solution provider for portable spot cooling applications, Koldwave has the experience and product breadth to ensure you have the right air-cooled and water-cooled air-conditioning systems for your business and job-specific applications. Simple to move, install, and operate, our rugged yet quiet units can be used for temporary, spot, emergency, or supplemental cooling in a variety of settings.

Working with you, we can determine what models make the most sense for you and your customers, as well as provide smart recommendations for growing your spot cooling business. You will also have our U.S.-based sales and service team on call to ensure everything remains business as usual, providing you with free, ongoing technical support and prompt resolution if a problem ever occurs.

- Server / Telecommunications Rooms
- Elevator / Mechanical Rooms
- Light-Industrial / Factories
- Commercial Spaces / Offices
- Industrial Kitchens
- Hospitals
- Automotive Garages
- Outdoor Events
- Apartments

Air-Cooled Portable Air Conditioners

Koldwave Air-Cooled Portable Air Conditioner Equipment is an effective, smart solution to your temporary climate control needs. By ducting air to an unoccupied space, our complete line of units is capable of delivering cooling capacities that range from 10,000 to 144,000 BTU/hr. In addition, Koldwave units only use an environmentally friendly refrigerant (R-410A), feature a digital control panel, and are available with a number of field-installed accessories.

Water-Cooled Portable Air Conditioners & Heat Pumps

When venting condenser air is not an option, Koldwave's water-cooled units provide you with an effective, efficient climate control solution for permanent or temporary applications. Koldwave Water-Cooled Portable Air Conditioners and Heat Pumps utilize a steady supply of water to provide cooling and heating capacities that range from 6,300 to 23,000 BTU/hr and heating capacities from 7,000 to 27,300 BTU/hr. With standard features such as integrated controls with self diagnostics, internal condensate pump, water reg valves, refrigerant service ports and side quick connect piping connectors that simplify field installation.

Split System Air Conditioning Equipment

Our split system AC units offer ease of installation for temporary or permanent installations. They provide 12,000 or 22,000 BTU/hr of cooling capacity. This unique "indoor unit" features a self-contained water-cooled refrigeration circuit with integrated controls, fluid pump, condensate pump and glycol reservoir. The remote fluid cooler or "outdoor unit" is provided with a 25 ft water/power line with quick-connect connections that easily interconnect the two units. Single source power supply on the "indoor unit" provides the power for the "outdoor unit."

"Custom Built" Industrial Air Conditioning & Heating Equipment

Koldwave industrial equipment is offer in cooling capacities from 36,000 - 360,000 BTU/hr (10-150 KW) 34,130 – 512,000 BTU/hr heating capacity. These units are built to order and provide a wide range of options to that can be provided. These options include electrical power options, electric heaters, Hour Meters, Hot Gas By-Pass, Variable Frequency Drives, (up to 3" ESP), Dehumidification Modes, Terminal or Cam-lock Power Connections, Flooded Condenser Low Ambient, and more.

Air-Cooled Portable Air Conditioner Equipment

6CC10 - SPOT COOLING/ROOM COOLING/DEHUMIDIFICATION



Standard Features

- Spot Cool/Room Cool Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- Thermostatic Control with Multi-Speed Fan
- Separate Direct Drive Fan Motors
- Optional Directional Nozzle (1)
- Self-Diagnostic System
- Off-Timer
- Washable Filters
- Humidity Control Function
- Includes Built-in Condensate Pump
- Auto/Manual Fan Speed Option
- R-410A Refrigerant

Optional Accessories

- Portable Kit with Wheels and Nozzle
- Server Rack Mounting Kit
- Ceiling Hanging Kit
- Stacking Kit
- 6" Exhaust Flange



STACK



SINGLE



RACK



MODEL	COOLING CAPACITY BTU/HR	COOLING TEST CONDITIONS	VOLTAGE/PHASE/HERTZ	AMPERAGE	FUSE SIZE (AMPS)*	LCDI PLUG CONFIGURATION	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT	CONDENSATE PUMP
6CC10	10,000	95°DB/83°WB	115/1/60	10	15	NEMA 5-15P	269 Sq Ft	20" X 17.2" X 24"	128 Lbs	Included

6KK14 & 6KK17 - SPOT COOLING/ROOM COOLING



Standard Features

- Spot Cool/Room Cool Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- Thermostatic Control with Multi-Speed Fan
- Double Shaft Motor for Two Fans
- Directional Nozzles (2)
- Heavy-Duty Twin Wheel Casters for Portability
- Self-Diagnostic System
- Off-Timer
- Washable Filters
- R-410A Refrigerant


Optional Accessories

- Easy Install Condensate Pump Kit with Overflow Protection
- Remote Controller with 26' Line
- 16' Temperature Sensor Line
- Condenser Discharge Kit
- Condenser Return Air Plenum




MODEL	COOLING CAPACITY BTU/HR	COOLING TEST CONDITIONS	VOLTAGE/PHASE/HERTZ	AMPERAGE	FUSE SIZE (AMPS)*	LCDI PLUG CONFIGURATION	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT	CONDENSATE TANK CAPACITY
6KK14	13,200	95°DB/83°WB	115/1/60	11.5	15	NEMA 5-15P	355 Sq Ft	41" x 20.6" x 26.4"	161 Lbs	4.75 GAL
6KK17	16,800	95°DB/83°WB	115/1/60	15.5	20	NEMA 5-20P	431 Sq Ft	41" x 20.6" x 26.4"	205 Lbs	4.75 GAL

CONDENSER RETURN ADAPTER



CONDENSATE PUMP



CONDENSER DISCHARGE KIT



* Time delay fuses and circuit breakers are recommended.

6KK21 - SPOT COOLING/ROOM COOLING

Standard Features

- Compressor Time Delay
- Compressor Overload Protection
- High Pressure Switch
- Anti-Freeze Thermostat
- Self-Diagnostic System
- Automatic Restart
- Auto/Manual Fan Speed Option
- R-410A Refrigerant

Optional Accessories

- Easy Install Condensate Pump Kit with Overflow Protection
- Remote Controller with 26' Line
- 16' Temperature Sensor Line
- Condenser Discharge Kit
- Condenser Return Air Plenum



MODEL	COOLING CAPACITY BTU/HR	COOLING TEST CONDITIONS	VOLTAGE/PHASE/HERTZ	AMPERAGE	FUSE SIZE (AMPS)*	LCDI PLUG CONFIGURATION	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT	CONDENSATE TANK CAPACITY
6KK21	21,000	95°DB/83°WB	230/1/60	10	11	NEMA 6-15P	538 Sq Ft	41" X 20.6" X 26.4"	216 LBS	4.75 GAL

5KK30 & 6KK37 - SPOT COOLING/ROOM COOLING

Standard Features

- Spot Cool/Room Cool Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- Thermostatic Control with Multi-Speed Fan
- Heavy-Duty Twin Wheel Casters for Portability
- Self-Diagnostic System
- Off-Timer
- Washable Filters
- R-410A Refrigerant


Optional Accessories

- Easy Install Condensate Pump Kit with Overflow Protection
- Remote Controller with 26' Line
- 16' Temperature Sensor Line
- Condenser Discharge Kit
- Condenser Return Air Plenum




MODEL	COOLING CAPACITY BTU/HR	COOLING TEST CONDITIONS	VOLTAGE/PHASE/HERTZ	AMPERAGE	FUSE SIZE (AMPS)*	LCDI PLUG CONFIGURATION	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT	CONDENSATE TANK CAPACITY
5KK30	29,000	95°DB/83°WB	230/1/60	16	20	NEMA 6-20P	754 Sq Ft	47.3" X 22" X 29.4"	238 Lbs	4.75 GAL
6KK37	37,000	95°DB/83°WB	230/1/60	19.5	30	NEMA 6-30P	1076 Sq Ft	54.3" X 26" X 34.8"	275 Lbs	4.75 GAL

CONDENSER RETURN ADAPTER



CONDENSATE PUMP



CONDENSER DISCHARGE KIT



* Time delay fuses and circuit breakers are recommended.

Air-Cooled Portable Air Conditioner Equipment

6KK61 & 6KK92 - SPOT COOLING/ROOM COOLING



Standard Features

- Spot Cool/Room Cool Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- Separate Direct Drive Fan Motors
- Digital Control Panel
- Condensate Pump with Overflow Protection
- Directional Nozzles (3)
- Heavy-Duty Twin Wheel Casters for Portability
- Washable Filters
- Self-Diagnostic System
- Off-Timer
- 20" Hot Air Exhaust Flange
- R-410A Refrigerant
- Hot Gas Bypass (6KK92)
- Power Cord with Arc Fault Protection (6KK61)
- Terminal Electrical Connection (6KK92)

Optional Accessories

- Remote Controller with 26' Line
- 16' Temperature Sensor Line
- Condenser Discharge Kit
- Condenser Return Air Plenum



MODEL	COOLING CAPACITY BTU/HR	COOLING TEST CONDITIONS	VOLTAGE/PHASE/HERTZ	AMPERAGE	FUSE SIZE (AMPS)*	ELECTRICAL CONFIGURATION	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT	CONDENSATE PUMP
6KK61	61,000	95°DB/83°WB	230/1/60	32	40	Hard Wired	1722 Sq Ft	60" X 29" X 51.5"	694 Lbs	Included
6KK92	92,000	95°DB/83°WB	460/3/60	17.2	20	Hard Wired	2637 Sq Ft	60" X 29" X 51.5"	794 Lbs	Included

6HK16 - SPOT COOLING/ROOM COOLING/HEAT PUMP



Standard Features

- Spot Cool/Room Cool Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- Thermostatic Control with Multi-Speed Fan
- Directional Nozzles (2)
- Heavy-Duty Twin Wheel Casters for Portability
- Auto Fan Speed Option
- Self-Diagnostic Function
- Off-Timer
- Washable Filters
- R-410A Refrigerant


Optional Accessories

- Easy Install Condensate Pump Kit with Overflow Protection
- Remote Controller with 26' Line
- 16' Temperature Sensor Line
- Condenser Discharge Kit
- Condenser Return Air Plenum




MODEL	COOLING CAPACITY BTU/HR	HEATING CAPACITY BTU/HR	COOLING TEST CONDITIONS	VOLTAGE/PHASE/HERTZ	AMPERAGE	FUSE SIZE (AMPS)*	LCDI PLUG CONFIGURATION	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT	CONDENSATE TANK CAPACITY
6HK16	16,800	18,500	95°DB/83°WB	115/1/60	16	20	NEMA 5-20P	430 Sq Ft	49" X 24" X 30"	251 Lbs	4.75 GAL

CONDENSER RETURN ADAPTER



CONDENSATE PUMP



CONDENSER DISCHARGE KIT



* Time delay fuses and circuit breakers are recommended.

6SS12 & 6SS24 - SPLIT SYSTEM COOLING

Standard Features

- Compressor Time Delay
- Compressor Overload Protection
- High Pressure Switch
- Thermostat
- Anti-Freeze Thermostat
- Self-Diagnostics
- Automatic Restart
- Pre-Charged Glycol Lineset w/Quick Connect Fittings
- Quick Connect Communications Between Indoor and Outdoor Units
- Condensate Pump
- Internal Glycol Reservoir
- Internal Fluid Pump
- Indoor unit – Self-Contained Water Cooled AC
- Outdoor Unit – Remote Fluid Cooler
- Quick Connect 25 ft Pre-Charged Glycol/Power Line Sets



MODEL	COOLING CAPACITY BTU/HR	VOLTAGE/PHASE/HERTZ	FUSE SIZE (AMPS)*	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D		SHIP WEIGHT	
					INDOOR	OUTDOOR	INDOOR	OUTDOOR
6SS12	12,000	115/1/60	15	355 Sq Ft	36.54" X 27.75" X 13.78"	25.79" X 23.62" X 10.83"	183 Lbs	48.5 Lbs
6SS24	22,000	220/1/60	15	646 Sq Ft	36.54" X 27.75" X 13.78"	27.56" X 27.56" X 10.83"	205 Lbs	59.52 Lbs

6HK - HIGH CAPACITY COOLING

Standard Features

- All Steel, Painted Cabinets
- Internal Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- Cleanable Vinyl Chloride Air Filter
- Fork Lift Slots and Lifting Lugs Standard
- Heavy-Duty 4 Wheel Casters
- R-410A Refrigerant
- Return Duct Dia Connection Evap 16"
- Operating Temp 64 - 113°F



MODEL	COOLING CAPACITY BTU/HR	VOLTAGE/PHASE/HERTZ	SUPPLY DUCT DIA CONNECTION EVAP/CONDENSER	RETURN DUCT DIA CONNECTION EVAP/CONDENSER	AMP DRAW	OPERATING TEMPERATURE	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT	CONDENSATE
6HK60	60,000	230/1/60	16" / 20"	16" / N/A	32 A	64-113°F	1830 Sq Ft	58.1" X 29.5" X 62.1"	661 Lbs	Drain
6HK144	144,400	230/3/60	14" (2) / 18" (2)	14" (2) / 18" (2)	54 A	64-113°F	3767-4951 Sq Ft	71" X 34.3 X 75"	1168.4 Lbs	Drain
6HK144	144,400	460/3/60	14" (2) / 18" (2)	14" (2) / 18" (2)	27 A	64-113°F	3767-4951 Sq Ft	71" X 34.3 X 75"	1168.4 Lbs	Drain

* Time delay fuses and circuit breakers are recommended.

Water-Cooled Portable Air Conditioner & Heat Pump Equipment

5WK07 - ROOM COOLING/HEAT PUMP



Standard Features

- Sleek Stainless Steel Cabinet
- Internally Insulated with Fiberglass Insulation
- Forward Curve Fan with Direct Drive Motor
- R-410A Refrigerant
- 15 Amp Breaker
- Coaxial Copper Condenser Coil
- Touch Pad Electronic Control
- Condensate Pump
- Rotary Compressor
- Thermostatic Control with Multi-Speed Fan
- Off-Timer
- Quick Connect Water Hose Kit

- Automatic Water Regulating Valve
- 4-Way Adjustable Air Discharge Grilles
- 18" Hose Kit

Optional Accessories

- 10', 20', 40' Hose Kits
- Remote Controller



MODEL	COOLING CAPACITY BTU/HR	HEATING CAPACITY BTU/HR	COOLING TEST CONDITIONS	VOLTAGE/ PHASE/ HERTZ	AMPERAGE	FUSE SIZE (AMPS)**	LCDI PLUG CONFIGURATION	GPM @ 85°F ENTERING WATER	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT
5WK07	6300	7,000*	80°DB/67°WB	115/1/60	9.2	15	NEMA 5-15P	1.85	170 sq. ft.	17.6" X 22.4" X 12"	89 Lbs

5WK14 - ROOM COOLING/HEAT PUMP



Standard Features

- Sleek Stainless Steel Cabinet
- Internally Insulated with Fiberglass Insulation
- Forward Curve Fan with Direct Drive Motor
- R-410A Refrigerant
- 15 Amp Breaker
- Coaxial Copper Condenser Coil
- Touch Pad Electronic Control
- Condensate Pump
- Rotary Compressor
- Thermostatic Control with Multi-Speed Fan
- Washable Filters
- Off-Timer
- Quick Connect Water Hose Kit
- Automatic Water Regulating Valve
- 4-Way Adjustable Air Discharge Grilles
- 18" Hose Kit

Optional Accessories

- 10', 20', 40' Hose Kits
- Remote Controller



MODEL	COOLING CAPACITY BTU/HR	HEATING CAPACITY BTU/HR	COOLING TEST CONDITIONS	VOLTAGE/ PHASE/ HERTZ	AMPERAGE	FUSE SIZE (AMPS)**	LCDI PLUG CONFIGURATION	GPM @ 85°F ENTERING WATER	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT
5WK14	10,800	12,200*	80°DB/67°WB	115/1/60	11.6	15	NEMA 5-15P	2.99	290 sq. ft.	31.5" X 25" X 10.2"	131 Lbs

18" HOSE KIT



20" HOSE KIT



* Heat pump units require 50°F minimum water inlet temperature during the heating mode.

**Time delay fuses and circuit breakers are recommended

6WK16 - SPOT COOLING/ROOM COOLING

Standard Features

- Spot Cool/Room Cool Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- Optional Easy Install Condensate Pump Kit with overflow protection
- R-410A Refrigerant
- 15 Amp Breaker
- Directional Nozzles (2)
- Self-Diagnostic System
- Thermostatic control with Multi-Speed Fan
- Heavy-Duty 4 Wheel Casters
- 17' Quick Connect Hose Kit
- Automatic Water Regulating Valve
- Rotary Compressor
- Washable Filters

Optional Accessories

- Easy Install Condensate Pump Kit with Overflow Protection



MODEL	COOLING CAPACITY BTU/HR	COOLING TEST CONDITIONS	VOLTAGE/PHASE/HERTZ	AMPERAGE	FUSE SIZE (AMPS)**	LCDI PLUG CONFIGURATION	GPM @ 85°F ENTERING WATER	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT
6WK16	16,000	95°DB/67°WB	115/1/60	13	15	NEMA 5-15P	1.36	430 Sq Ft	41" x 20.6" x 26.4"	201 Lbs

5WK18 & 5WK26 - ROOM COOLING/HEAT PUMP



Standard Features

- Sleek Stainless Steel Cabinet
- Internally Insulated with Fiberglass Insulation
- Forward Curve Fan with Direct Drive Motor
- R-410A Refrigerant
- 15 Amp Breaker
- Coaxial Copper Condenser Coil
- Touch Pad Electronic Control
- Condensate Pump
- Rotary Compressor
- Thermostatic Control with Multi-Speed Fan
- Heavy-Duty Casters
- Off-Timer

- Quick Connect Water Hose Kit
- Automatic Water Regulating Valve
- 4-Way Adjustable Air Discharge Grilles
- Rotary Compressor
- Washable Filters

Optional Accessories

- 10', 20', 40' Hose Kits



MODEL	COOLING CAPACITY BTU/HR	HEATING CAPACITY BTU/HR	COOLING TEST CONDITIONS	VOLTAGE/PHASE/HERTZ	AMPERAGE	FUSE SIZE (AMPS)**	LCDI PLUG CONFIGURATION	GPM @ 85°F ENTERING WATER	APPROX COOLING AREA	UNIT DIMENSIONS H X W X D	SHIP WEIGHT
5WK18	16,100	19,100	80°DB/67°WB	230/1/60	6.6	15	NEMA 6-15P	4.00	430 sq. ft.	28.8" X 36" X 12.3"	201 Lbs
5WK26	23,000	27,300	80°DB/67°WB	230/1/60	10	15	NEMA 6-15P	4.90	618 sq. ft.	28.8" X 36" X 12.3"	201 Lbs

18" HOSE KIT



20" HOSE KIT



* Heat pump units require 50°F minimum water inlet temperature during the heating mode.

**Time delay fuses and circuit breakers are recommended

Custom Industrial AC & Heating Equipment

HORIZONTAL UNITS - COOLING ONLY, COOLING WITH ELECTRIC HEAT, HEAT PUMPS & DEHUMIDIFICATION OPTIONS



Standard Features

- Unit Capacities: 3, 5, 12, 20, 25 and 30 Ton
- Duct Collars
- Evaporator Stainless Steel Drain Pan
- R-410A Refrigerant
- Terminal Block Power Connection
- Phase Reversal Indicator Light
- Durable White Powder Coat Finish
- Condenser Coil Guard
- Threaded Condensate Drain Connection
- Main Circuit Breaker
- Pleated Filters
- Mode Selector Switch
- 4-Way Lifting Pod
- Casters

Optional Accessories

- Camlock Power-In Connectors
- Duct Collar Covers
- Ductable Condenser Discharge
- Hour Meter
- Casters, Swivel/Lockable
- Quarter Turn Access Panel Fasteners
- Remote Thermostat w/Cable
- Trailer Mounted
- Electric Heat 10kW-60kW
- Phase Reversal Indicator



Note: Products can be configured with select features and a wider variety of options than what are listed here. Please contact Koldwave to discuss special features, paint colors, capabilities and configurations.

MODEL	CAPACITY TONS	VOLTAGE/PHASE/HERTZ	UNIT DIMENSIONS H X W X L	APPROX. WEIGHT	MCA	MODEL	CAPACITY TONS	VOLTAGE/PHASE/HERTZ	UNIT DIMENSIONS H X W X L	APPROX. WEIGHT	MCA
HKW3N	3	208/230/1/60	54.5" X 29.5" X 67"	590 Lbs	38.9	HKW25	25	208/230/3/60	57" X 95.5" X 95.5"	3000 Lbs	162.4
HKW5N	5	208/230/1/60	54.5" X 29.5" X 67"	690 Lbs	55.6	HKW30	30	208/230/3/60	67" X 95.5" X 95.5"	3200 Lbs	180.8
HKW12M	12	208/230/3/60	71" X 34.5" X 78"	1500 Lbs	59.6	HPKW5N Heat Pump	5	208/230/1/60	48.5" x 29.5" x 67"	705 Lbs	55.6
HKW20	20	208/230/3/60	57" X 95.5" X 95.5"	2780 Lbs	130.1						

Note: HKW20-30 ton units also available mounted on DOT approved trailer assembly.

Air-Cooled Portable Air Conditioner Equipment

TRAILER MOUNTED UNITS - COOLING ONLY, COOLING WITH ELECTRIC HEAT & DEHUMIDIFICATION OPTIONS



Standard Features

- Duct Collars
- Evaporator Stainless Steel Drain Pan
- R-410A Refrigerant
- Camlock Color Coded In Connectors
- Phase Reversal Indicator Light
- Durable White Powder Coat Finish
- Condenser Coil Guard
- Threaded Condensate Drain Connection
- Main Circuit Breaker
- Pleated Filters
- Mode Selector Switch



MODEL	CAPACITY TONS	VOLTAGE/PHASE/HERTZ	UNIT DIMENSIONS H X W X L	APPROX. WEIGHT	MCA
HKW-20-TR	20	208/3/60	75" X 94" X 160"	3887 Lbs	130.1
HKW-25-TR	25	208/3/60	75" X 94" X 160"	4107 Lbs	162.4
HKW-30-TR	30	208/3/60	85" X 94" X 160"	4327 Lbs	180.8

VERTICAL UNITS - COOLING ONLY, COOLING WITH ELECTRIC HEAT OPTIONS

Standard Features

- Unit Capacities: 5, 10 and 20 Ton
- Bi-Directional Discharge Grille
- Return Air Grille
- Evaporator Stainless Steel Drain Pan
- 4-Way Lifting Pod
- R-410A Refrigerant
- Terminal Block Power Connection
- Phase Reversal Indicator
- Durable White Powder Coat Finish
- Guards on Condenser Inlet and Discharge
- Single Drain Port on Condenser Base
- Hose Connection Condensate Drain
- Circuit Breaker
- Cleanable Filter
- Mode Switch
- Unit Mounted Thermostat

Optional Accessories

- Camlock Power Connectors In and Out
- Recessed Gauge Panel
- Hour Meter
- Tent Clamps
- Quarter Turn Access Panel Fasteners
- Remote Thermostat w/Cable
- Electric Heat, 10kW-45kW
- Ductable Supply/Return Air Plenums
- Top Condenser Air Discharge (VAD only)
- Hot Gas Bypass
- Waterproof Base Coating
- Condenser Air Deflector
- Emergency Power Off Switch
- Casters, Swivel/Lockable (5 Ton only)
- Low Ambient Flooded Condenser



MODEL	CAPACITY TONS	VOLTAGE/PHASE/HERTZ	UNIT DIMENSIONS H X W X L	APPROX. WEIGHT	MCA
KWV-5	5	230/3/60	64.5" X 47.4" X 32.5"	670 Lbs	30.6
KWV-10	10	230/3/60	83" X 65.5" X 35.5"	1360 Lbs	57
KWV-20	20	230/3/60	94.1" X 91.6" X 36"	2200 Lbs	97.2

Notes:

1. Models KWV-5 – 10 have integral plenum assemblies included in the height dimensions shown.
2. KWV-20: Overall height indicated includes 12" high removable plenum assembly for front free-blow supply. Duct collar adapters are available for both supply and return air.

Electric Heating

KWHH - HORIZONTAL HEATING UNITS AND INLINE BLOWER



Standard Features

- Duct Collars
- Durable Finned Tubular Heating Elements
- Terminal Block Power Connection
- Power Indicator Light
- White Powder Coat Finish
- Casters (Swivel/Lockable)
- Main Circuit Breaker
- Cleanable Filters
- Mode Switch
- Unit Mounted Thermostat

Optional Accessories

- Hour Meter
- Camlock In Power Connections
- Quarter Turn Fasteners on Access Panels
- Insulated Inlet Air Section
- Fork Lift Pockets



MODEL	KW	VOLTAGE/PHASE/HERTZ	UNIT DIMENSIONS H X W X D	SHIP WEIGHT	MCA
KHH15	15	208/3/60	46.5" X 34" X 55"	444 Lbs	62.5
KHH30	30	208/3/60	46.5" X 34" X 55"	460 Lbs	114.6
KHH45	45	208/3/60	46.5" X 34" X 55"	480 Lbs	166.6
KHH60	60	208/3/60	46.5" X 34" X 55"	495 Lbs	258.9
KHH150	150	460/3/60	52.75" X 48" X 76"	1290 Lbs	258.5
InLine Blower KWIB5 5000 CFM	N/A	460/3/60	51.5" X 38" X 52"	582 Lbs	14.4

Equipment Leasing Program

Features and Benefits

- No Down Payment
- Low Monthly Payments
- 100% Tax Write Off
- Improve Balance Sheet
- No Business Lien
- Rent or Sell From Inventory
- Higher Return on Investment
- Simple On-Line Application
- Assures Inventory at Peak Times

Terms and Conditions

- \$50,000 Minimum Order
- 36 Month Lease Terms
- Freight Allowed
- Standard or Seasonal Payment Program

Simple Three Step Process

1. Contact your local representative or presale support at info@koldwave.com.
2. Apply for Koldwave lease online at www.koldwave.com.
3. Place equipment order with your local representative.



LIKE YOU, KOLDWAVE STAYS COOL UNDER PRESSURE.

To learn more, visit us online or contact us directly.

Koldwave, Inc.
260 North Elm Street Westfield, MA 01085
www.Koldwave.com
Tel: 413.564.5520 | Fax 413.564.5815