

STANDARD CONSTRUCTION

FRAME: 18-GA. galvanized steel, channel type.

BLADE: 18-GA. galvanized steel.

SHAFT: 1/2" diameter plated steel stub mechanically fastened to blade with a monobolt.

BEARINGS: Self lubricated bronze Oilite.

LINKAGE: Chevron type formed bracket of $\frac{1}{8}$ " thick plated steel. Trunnion is a machined pivot of plated steel with a $\frac{5}{16}$ " diameter rod.

SEALS: Stainless steel at jambs.

SCREEN: On exterior face, (when indicated)

1/2" sq. mesh, 19-GA. galvanized steel (.041").

FINISH: Mill.

OPTIONS

Frames and Blades of other gauges

Other materials - Stainless steel, Copper, Aluminum, etc.

Neoprene blade edge seals

Finishes - Enamels, Epoxies, etc.

Screens - Insect screen 18_{16} aluminum mesh, .011".





-or- 1/2" flattened aluminum, .051" thk.,

-or- 1/4" sq. mesh, 18-GA. galvanized steel, .047",


-or- 1/2" sq. mesh, 16-GA. stainless steel, .063".

NOTES

1. Nominal deductions will be made to the opening size given.
2. Approximate shipping weight is 7.5 lbs./sq.ft.



Flange Frame available.



										
Item #	Qty	Width	Height	Width	Height	Mullion	Type	Location		
		Opening Size		Louver Size			Screens			<u>Union Made</u>
Arch. / Eng. :						EDR:		ECN:		Job:
Contractor:										
Project:						Date:		DWN:		DWG:

In the interest of product development, Louvers & Dampers reserves the right to make changes without notice.


PERFORMANCE DATA

Pressure Drop: .16 in. w.g. at 1050 fpm


Free Area: 7.03 sq.ft. = 43.9% for 48"W x 48"H sample tested in accordance with AMCA Standard 500-L.

Beginning Point of Water Penetration: 1002 (fpm)

Ratings do not include the effects of a screen.



Intake air converted to standard air density.
Tested to AMCA Standard 500-L, Figure 5.5.



1002 (FPM) Beginning Point of Water Penetration.

Free Area (sq. ft.)

		Width (in.)								
		12"	18"	24"	30"	36"	42"	48"	54"	60"
Height (in.)	12"	.21	.34	.47	.60	.73	.86	.99	1.12	1.26
	24"	.63	1.03	1.43	1.83	2.23	2.63	3.03	3.34	3.83
	36"	1.08	1.76	2.45	3.13	3.81	4.50	5.18	5.86	6.54
	48"	1.47	2.40	3.33	4.26	5.19	6.12	7.03	7.98	8.91
	60"	1.85	3.01	4.18	5.35	6.61	7.68	8.84	10.01	11.18
	72"	2.28	3.72	5.16	6.60	8.04	9.48	10.92	12.36	13.80
	84"	2.73	4.45	6.18	7.90	9.62	11.35	13.07	14.79	16.52
	96"	3.11	5.08	7.04	9.00	10.97	12.93	14.90	16.86	18.83