

ALSEP45S

STANDARD MATERIALS AND CONSTRUCTION

LOUVER: Frame and blade are .081" thk. (nominal) extruded aluminum 6063-T52/T6 alloy, w/ post

corner construction.

SCREEN: (When indicated, in a removable frame)

½" flattened aluminum, .051" thk.,

Insect screen 18/16 aluminum mesh, .011" dia., -or-

-or-1/2" sq. mesh intermediate double crimped

aluminum wire, .063" dia.

FINISH: Varies.

SIZE: 38" x 38" x 18", sits on a curb 12" - 36" high.

CURB: 12 GA. Galvanneal, galvanized steel or 1/8"

thk. (nominal) aluminum w/ 4" mounting flange,

welded construction.

ROOF: .060" thk. (nominal) formed aluminum with 1/2" thk. (nominal) rigid insulation.

POST CORNER: .081" thk. (nominal) formed aluminum.

GLASS: 1/8" thk. (nominal) annealed glass.

ROOF OPENING: 28" x 28" minimum, 38" x 38" maximum.

LOUVER DETAILS

MODEL: AS4B45H (Airline Louvers) SIZE: 30" x 18" (3) three required.

FREE AREA: 4.905 sq. ft. Total.

DAMPER DETAILS

MODEL: A1H Class I - 250° Smoke Damper

(Arrow United)

SIZE: 26" x 26" O.D. (nominal) **ACTUATOR:** Internally mounted power

close spring open (fail open) 120 VAC actuator w/ open/closed indicator.

CORE AREA: 4.38 sq. ft.

OPTIONS

- Hinged louver with hasp or surface mount latch in place of access door in curb.

NOTES

1. Actuator access door in ductwork supplied and installed by others.

Nominal Deductions will be made to the opening size given.

In the interest of product development. Airline Louvers reserves the right to make changes without notice

In the interest of product development, Afriline Louvers reserves the right to make changes without notice.									
									A STATE OF THE STA
Item #	Otv	Width	Height	Curb	Glass	Hinged	Tagging		
Item#	Qty	Roof Opening		Height	Access	Access	ragging		<u>Union Made</u>
Arch. / Eng. :				EDR:		ECN:		Job:	
Contractor:									
Project:				Date:		DWN:		DWG:	
1000 D.L. E. L. I. D.L. G. II. 205 D.L. E. L. I. MD 20007 D.L. (F70) 100 7070 F. (F70) 100 7070									

1020 Prince Frederick Blvd. Suite 305 • Prince Frederick, MD 20687 • Phone: (570) 420-7079 • Fax: (570) 420-7078



ALSEP45S

