



CSD-1 Manual Reset LWCO





- 1. Dimensions are approximate and should not be used to "rough-in" equipment.
- Dimensions are subject to change without notice.

BOILER CERTIFIED RATINGS & CAPACITIES

Fuel Type	Natural/Propane Gas	Boiler FLA	9.9*
Input BTU/hr.	1,500,000 / 440 kW	Min. Gas Pressure Required	5" W.C.**
Output BTU/hr.	1,275,000 / 374 kW	Max. Gas Pressure Allowed	14" W.C.
Electrical Requirements	120 VAC / 1 ph / 60 hz	Operating Weight	732 lbs. / 332 kg.

BOILER / WATER HEATER TRIM & CONTROLS

Main Gas Valve	V4944B	Main Ball Valve	1 1/4 "		
Firing Valve	1 1/4"	Pilot Regulator	White-Rodgers 25M		
Safety Valve	ASCO L8214G 1 1/4"	Air Switch	HUBA		
Ignition Control	Honeywell RM7897C	Blower Motor	Fasco 1/2 hp - FLA 8.2		
Operating Control (FB/FW)	Jumo	Relief Valve - FB	1" x 1 1/4" set @ 50 psi		
High Limit	Honeywell L4008E	Relief Valve - FW	3/4" x 3/4" set @ 125 psi		
		Flow Switch	TACO		

A.S.M.E.

ASME Sect IV Htg Surface	161.16 Sq. Ft. / 14.97 Sq. M.	Design Data	Max. 160 psig & 250°F
Water Volume	5.0 gal / 18.9 Liters		

- Add circulator amps.
- For incoming gas pressures lower than 5" W.C. natural or 11" W.C. propane, consult factory.

BOILER TEMPERATURE RISE / PRESSURE DROP

	20°F /	11.1°C			25°F /	13.9°C		30°F / 16.7°C				35°F / 19.4°C				
Flow	Rate	Pressui	re Drop	Flow	Rate	Pressu	Pressure Drop		Flow Rate		Pressure Drop		Flow Rate		Pressure Drop	
GPM	L/s	Ft	kPa	GPM	L/s	Ft	kPa	GPM	L/s	Ft	kPa	GPM	L/s	Ft	kPa	
127.5	8.0	3.57	10.5	102.0	6.4	2.36	7.0	85.0	5.4	1.70	5.0	72.9	4.6	1.30	3.7	

WATER HEATER HOURLY RECOVERY CAPACITY (GPH & LPH)

40°F	22°C	60°F	33°C	80°F	44°C	100°F	56°C	120°F	67°C	140°F	78°C
3741	14141	2494	9427	1870	7070	1496	5656	1247	4714	1069	4040

REP FIRM	
SUBMITTED BY	
JOB NAME	
ARCHITECT	
ENGINEER	
CONTRACTOR	
DATE	


FUTERA II 1500

Category I or Category III Appliance (see Installation and Operation Manual for venting information)



A Division of Mestek, Inc. Westfield, MA 01085 (413) 568-9571

OUTDOOR UNIT



FUTERA II 1500

- Dimensions are approximate and should not be used to "rough-in" equipment.
 Dimensions are subject to change without notice.