SPECTRUM 250 Category I Appliance 25 1/8 in Must be vented into a negative pressure vent system. [63.8 cm] 6 21/32 in [16.9 cm] FOR INDOOR -Ø 1 1/2" NPT WATER (2 PLCS.) 32 in [81.3 cm] Ø8 in [Ø20.3 cm] Ø16 in 00 [Ø40.6 cm] 00 29 5/8 in [75.2 cm] 17[']in [43.2 cm] 1 1/2 in 16 11/32 in [3.8 cm] [41.5 cm] 2 5/16 in [5.9 cm] [27.9 cm] 13 in [[33.0 cm] Ø 3/4" GAS 24 1/4 in [61.6 cm] [29.8 cm] 4 7/32 in 10 3/4 in [10.7 cm] [27.3 cm] TOP LEFT SIDE 29 5/8 in 26 1/4 in [75.3 cm] [66.7 cm] 13 1/8 in [33.3 cm] 8 1/4 in [21.0 cm] 32 7/8 in [83.5 cm] 42 1/4 in [107.3 cm] 4 1/2 in [11.4 cm] 7 in 12 1/4 in 3/4 in †[17.8 cm] [31.1 cm] [1.9 cm] **FRONT** RIGHT SIDE

NOTE: FOR OUTDOOR ONLY

RSUB-4-C

- Notes:

 1. Dimensions are approximate and should not be used to "rough-in" equipment.

 2. Dimensions are subject to change without notice.

BOILER CERTIFIED RATINGS & CAPACITIES

Fuel Type	Natural/Propane Gas	Boiler FLA	1*
Input BTU/hr.	250,000 / 73 kW	Min. Gas Pressure Required	5" WC**
Output BTU/hr.	205,000 / 60 kW	Max. Gas Pressure Allowed	14" WC
Electrical Requirements	120VAC / 1 ph / 60 hz	Operating Weight	218 lbs. / 99 kg.

BOILER / WATER HEATER TRIM & CONTROLS

Gas Valve - INT	Honeywell VR8304M 3/4"	Ignition Control (SB)	Honeywell S9361A2085
Gas Valve	Honeywell VR8304Q 3/4"- 2 Stg.	Ignition Control (SW)	Honeywell S86IOM
Operating Control (SB/SW)	Honeywell - On/Off	Relief Valve - SW	3/4" x 3/4" set @ 125 psi
Operating Control (SW)	Jumo - 2 Stage	Relief Valve - SB	3/4" x 3/4" set @ 30 psi
High Limit (SB/SW)	Jumo	Flow Switch	TACO

A.S.M.E.

ASME Sect IV Htg Surface	36.7 Sq. Ft. / 3.41 Sq. M.	Design Data	Max. 160 psig & 250°F
Water Volume	1.3 gal / 4.85 Liters		

 ^{*} Add circulator amps.

BOILER TEMPERATURE RISE / PRESSURE DROP

10°F / 5.5°C					_				
	Flow	Rate	Pressui	re Drop	Flow	Rate	Pressui	re Drop	-
	GPM	L/s	Ft	kPa	GPM	L/s	Ft	kPa	-
	41.0	2.6	0.49	1.4	20.5	1.3	0.14	0.4	2 Pass
	41.0	2.6	3.54	10.4	20.5	1.3	0.98	2.9	4 Pass

WATER HEATER HOURLY RECOVERY CAPACITY (GPH & LPH)

40°F	22°C	60°F	33°C	80°F	44°C	100°F	56°C	120°F	67°C	140°F	78°C
600	2269	400	1513	300	1134	240	908	200	756	171	648

Spectrum 250 model boiler not available for sale in the U.S. market due to DOE regulations.

REP FIRM	
SUBMITTED BY	
JOB NAME	
ARCHITECT	
ENGINEER	
CONTRACTOR	
DATE	

SPECTRUM 250

Category I Appliance

Must be vented into a negative pressure vent system.



A Division of Mestek, Inc. Westfield, MA 01085 (413) 564-5515

^{**} For incoming gas pressures lower than 5" WC natural or 11" WC propane, consult factory.