#### **SPECTRUM 400 Category I Appliance** 25 1/8 in Must be vented into a negative pressure vent system. [63.8 cm] 6 21/32 in [16.9 cm] FOR INDOOR 32 in Ø 1 1/2" NPT WATER (2 PLCS.) [81.3 cm] Ø10 in [Ø25.4 cm] 00 17 in 00 29 5/8 in [75.2 cm] Ø20 in [Ø50.8 cm] [43.2 cm] 1 1/2 in 13 in [3.8 cm] [33.0 cm] 2 5/16 in Ø 3/4" GAS [5.9 cm] 16 11/32 in 11 in [27.9 cm] [41.5 cm] 11 3/4 in 34 3/8 in [29.8 cm] [87.3 cm] 4 7/32 in 10 3/4 in [10.7 cm] [27.3 cm] LEFT SIDE TOP 29 5/8 in 36 3/8 in [75.3 cm] [92.4 cm] 18 3/16 in [46.2 cm] 10 1/4 in [26.0 cm] 44 1/4 in [112.4 cm] 32 7/8 in [83.5 cm] 4 1/2 in [11.4 cm] 17 1/8 in 3/4 in [1.9 cm] [17.8 cm] [43.5 cm] RIGHT SIDE **FRONT**

NOTE: FOR OUTDOOR ONLY

RSUB-7-C

- Notes:

  1. Dimensions are approximate and should not be used to "rough-in" equipment.

  2. Dimensions are subject to change without notice.

#### **BOILER CERTIFIED RATINGS & CAPACITIES**

Fuel Type	Natural/Propane Gas	Boiler FLA	1*
Input BTU/hr.	399,000 / 117 kW	Min. Gas Pressure Required	5" WC**
Output BTU/hr.	323,988 / 95 kW	Max. Gas Pressure Allowed	14" WC
Electrical Requirements	120VAC / 1 ph / 60 hz	Operating Weight	264 lbs. / 120 kg.

### **BOILER / WATER HEATER TRIM & CONTROLS**

Gas Valve - INT	Honeywell VR8304M 3/4"	Ignition Control (SB On/Off)	Honeywell S9361A2085
Gas Valve	Honeywell VR8304Q 3/4"- 2 Stg	Ignition Control (SB 2 Stg.)	Honeywell S86IOM
Gas Valve	Honeywell VR8304Q 3/4"- 2 Stg.	Ignition Control (SW)	Honeywell S86IOM
Operating Control (SB)	Jumo - 2 Stage	Relief Valve - SW	3/4" x 3/4" set @ 125 psi
High Limit (SB/SW)	Jumo	Relief Valve - SB	3/4" x 3/4" set @ 30 psi
		Flow Switch	TACO

#### A.S.M.E.

ASME Sect IV Htg Surface	54.3 Sq. Ft. / 5.04 Sq. M.	Design Data	Max. 160 psig & 250°F		
Water Volume	1.5 gal / 5.64 Liters				

<sup>\*</sup> Add circulator amps.

# **BOILER TEMPERATURE RISE / PRESSURE DROP**

	30°F / 16.7°C				20°F / 11.1°C			10°F / 5.5°C				
	re Drop	Pressui	Rate	Flow	re Drop	Pressui	Rate	Flow	re Drop	Pressui	Rate	Flow
	kPa	Ft	L/s	GPM	kPa	Ft	L/s	GPM	kPa	Ft	L/s	GPM
2 Pass	0.7	0.20	1.4	21.6	1.4	0.47	2.0	32.4	5.0	1.69	4.1	64.8
4 Pass	4.7	1.60	1.4	21.6	10.0	3.40	2.0	32.4	-	-	-	-

# WATER HEATER HOURLY RECOVERY CAPACITY (GPH & LPH)

40°F	22°C	60°F	33°C	80°F	44°C	100°F	56°C	120°F	67°C	140°F	78°C
960	3630	640	2420	480	1815	384	1452	320	1210	274	1037

REP FIRM	
SUBMITTED BY	
JOB NAME	
ARCHITECT	
ENGINEER	
CONTRACTOR	
DATE	

# **SPECTRUM 400**

## **Category I Appliance**

Must be vented into a negative pressure vent system.



A Division of Mestek, Inc. Westfield, MA 01085 (413) 564-5515

<sup>\*\*</sup> For incoming gas pressures lower than 5" WC natural or 11" WC propane, consult factory.